LIRON LIGHTING

ALA1 Linear Series

LED Suspended Direct Linear Run Luminaire

Fixture Type:
Project Name:
Location:
Date:

Features:

-1 3/8" Wide advance architectural linear luminaire available in 2FT, 4FT and 8FT
- Direct lighting distribution
- 4 Lens options
- Various mounting option include suspended mount, wall mount and surface mount - see other spec sheet
- 120V continuous run up to 40FT and 277V up to 100FT



Product Performance Standard

Size	2FT/4FT/8FT	**Power Factor**	>0.9
Weight	3.75lb/6.1lb/12.5lb	**Life Span**	50,000 Hrs
Mounting	Pendant	**Dimmable**	1-10V Dimming
Color Temp	3000K/3500K/4000K	**Efficacy**	105lm/W
CRI	80	**Warranty**	5 Years
Input Voltage	120-277V	**Ambient Operation Temperature**	0C° (32°F) ~40C °(104°F)

Ordering Guide - (Linear Pandent direct linear run luminaire)

STEP 1

Fixture	Lens	CCT	Finish	Linear Feet
ALA1 Down light Version	D = diffuser C = Conves L = Louver R = Reflector	30K = 3000K 35K = 3500K 40K = 4000K	WH = White BK = Black	Nominal linear feet = In increments of 2'. fixture lengths com in 2'/4'/8' 120V continuous run up to 40 FT 277V continuous run up to 100 FT

Please continue the ordering steps on the next page.

Last Revised: 1/31/2022

10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.

LIRON LIGHTING

ALA1 Linear Series

LED Pendant Direct Linear Run Luminaire

Fixture Type:
Project Name:
Location:
Date:

Ceiling Type

STEP 2 - Please specify the ceiling type

****Ceiling type**

Dry Wall Ceiling Canopy

*AL-DWR4
= 4″ Round drywall Canopy

*AL-DWR2
= 2″ Square drywall Canopy

*AL-DWS4
= 4″ Square drywall Canopy

*AL-DWS2
= 2″ Round drywall Canopy

Drop Ceiling/on Grid

AL-TBR9F4
= T-Grid 9/16 Flat 4″ Round canopy

AL-TBR9F2
= T-Grid 9/16 Flat 2″ Round canopy

AL-TRS9S4
= T-Grid 9/16 Slot 4″ Round canopy

AL-TRS9S2
= T-Grid 9/16 Slot 2″ Round canopy

AL-TRB9F4
= T-Grid 15/16 Flat 4″Round canopy

AL-TBR15F2
= T-Grid 15/16 Flat 2″ Round canopy

AL-TBS15S4
= T-Grid 9/16 Slot 4″ Round canopy

AL-TBS15S2
= T-Grid 9/16 Slot 2″ Round canopy

Note: ** See page 4 for detailed ceiling type.
* 4″ is power feed canopy, 2″ is non power feed canopy.
Please specify if need to be custom.

Linear Run Connector

STEP - 3

Linear Run Connector

*AL-TC
= Inline connector

*Each in-line connector can be connect two fixtures
120V continuous run up to 40 FT
277V continuous run up to 100 FT

Optionals

Emergency Battery Backup

EM = 8W Emergency battery backup

Note: *Standard 1 EM PER RUN.
Not available in 2′ fixtures

10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.

LIRON LIGHTING

ALA1 Linear Series

LED Suspended Direct Linear Run Luminaire

Fixture Type:
Project Name:
Location:
Date:

Performance Data:

Lens	Diffuser	Louver	Micro Reflector	Convex
Lengths	2ft , 4ft , 8ft	2ft , 4ft , 8ft	2ft , 4ft , 8ft	2ft , 4ft , 8ft
Wattage	**20W/40W/80W**	**20W/40W/80W**	**20W/40W/80W**	**20W/40W/80W**
Efficacy	**75 lm/W**	**67 lm/W**	**100 lm/W**	**90 lm/W**
Beam Angle	Down 100°	Down 60°	Down 48°	Down 110°

Lens:



Diffuser
(-D)



Micro Reflector
(-R)



Louver
(-L)



Convex Lens
(-C)

Dimensions:



10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.

Line Connection:



Linear Connector
(-AL-TC)

120Vac: Connections up to 40 ft
277Vac: Connections up to 100ft



Mounting point:
24.72" for 2FT fixture
49.8"for 4FT fixture
100.08" for 8FT fixture

Continuous Run



Mounting point:
24.72" for 2FT fixture
49.8" for 4FT fixture
100.08" for 8FT fixture

Mounting point:
25.08" for 2FT fixture
50.28" for 4FT fixture
100.44" for 8FT fixture

Mounting point:
24.96" for 2FT fixture
50.04" for 4FT fixture
100.2" for 8FT fixture

10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com
Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.

Example Continue Runs Chart:

120Vac: Connections up to 40 ft
277Vac: Connections up to 100ft

Luminaire Run Length (ft)	Run Configuration	Line Joiner	5' Power Cable	5' Aircraft Cable	Canopy
2	2'	-	1	2	2
4	4'	-	1	2	2
6	4'+2'	1	1	3	3
8	8'	-	1	2	2
10	8'+2'	1	1	3	3
12	8'+4'	1	1	3	3
14	8'+4'+2'	2	1	4	4
16	8'+8'	1	1	3	3
18	8'+8'+2'	2	1	4	4
20	8'+8'+4'	2	1	4	4
22	8'+8'+4'+2'	3	1	5	5
24	8'+8'+8'	2	1	4	4
26	8'+8'+8'+2'	3	1	5	5
28	8'+8'+8'+4'	3	1	5	5
30	8'+8'+8'+4'+2'	4	1	6	6
32	8'+8'+8'+8'	3	1	5	5
34	8'+8'+8'+8'+2'	4	1	6	6
36	8'+8'+8'+8'+4'	4	1	6	6
38	8'+8'+8'+8'+4'+2'	5	1	7	7
40	8'+8'+8'+8'+8'	4	1	6	6
42	8'+8'+8'+8'+8'+2'	5	2	7	7
44	8'+8'+8'+8'+8'+4'	5	2	7	7
46	8'+8'+8'+8'+8'+4'+2'	6	2	8	8
48	8'+8'+8'+8'+8'+8'	5	2	7	7

10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.

LIRON LIGHTING

ALA1 Linear Series

LED Suspended Direct Pattern Run Luminaire

Fixture Type:
Project Name:
Location:
Date:

Ceiling Type:



Drop Ceiling / Off Grid



Sheetrock



Various "Hard Ceilings"



Drop Ceiling/Off Grid

Compatible for various T grid

- 9/16" Flat
- 15/16"Flat
- 9/16" Slot
- 15/16"Slot



9/16" Flat Ceiling



9/16" Step Ceiling



15/16" Flat Ceiling



15/16" Step Ceiling



4" Power Feed
Round Canopy
(-AL-DWR4)



2" Non-Feed
Round Canopy
(-AL-DWR2)



4" Power Feed
Square Canopy
(-AL-DWS4)



2" Non-Feed
Square Canopy
(-AL-DWS2)

10835 S Wilcrest Dr, Ste C Houston TX 77099 | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.