

## **2DD Series** 2nd Gen Disk Downlight

# **Fixture Type:** Project Name: Location:

**Dimension** 

#### **Features**

- -4"/6"/8" Aluminum Disk downlight
- -Single color temperature or CCT adjustable (3000K/4000K/5000K)
- -Triac dimming
- -Easy installation fit 3''/4''/5''/6'' J-box or 5"/6" Can
- -Optional battery backup
- -Architecture white finish standard, optional brushed nickle or oil bronze finish



Date:



Bronze












### **Product Performance Standard**

| Size          | 4"/6"/8"                    | Power Factor  | ≥90%            |
|---------------|-----------------------------|---------------|-----------------|
| Weight        | 2 lb                        | LED Lifespan  | 50,000 Hrs      |
| CRI           | 80                          | Dimmable      | Triac Dimming   |
| Color Temp    | Single Color/CCT Adjustable | Warranty      | 5 Years         |
| Input Voltage | e 120V                      | Ambient Opera | tion 0C° (32°F) |
|               | . = . ,                     | Temperature   | ~40C°(104°F)    |

#### **Ordering Guide** Example: LED2DD20W8IN3CT -BU



| F | ixture Type          | Wattage & Size   | Color Temp.                | Finish                             | Test Button               | Emergency Battery       |
|---|----------------------|------------------|----------------------------|------------------------------------|---------------------------|-------------------------|
|   |                      |                  |                            |                                    |                           |                         |
|   | LED2DD               | 10W4IN           | 30K = 3000K                | Blank = White<br>BN = Brush Nickle | Blank<br>BU = Test Button | Blank<br>EMJB12W = Jbox |
|   |                      | 15W6IN<br>20W8IN | 40K = 4000K<br>50K = 5000K | OB = Oil Broze                     | DO - Test bullott         | Emergency Battery       |
|   | 3CT = CCT Adjustable |                  |                            |                                    |                           |                         |





# **2DD Series** 2nd Gen Disk Downlight

| Fixture | Type: |
|---------|-------|
|---------|-------|

Project Name:

Location:

Date:

### **Performance Data**

|         | 3000K  |          | 4000K  |          | 5000K  |          |
|---------|--------|----------|--------|----------|--------|----------|
| WATTAGE | LUMEN  | EFFICACY | LUMEN  | EFFICACY | LUMEN  | EFFICACY |
| 10W     | 670lm  | 67lm/W   | 690lm  | 69lm/W   | 700lm  | 70lm/W   |
| 15W     | 950lm  | 63lm/W   | 980lm  | 65lm/W   | 1000lm | 67lm/W   |
| 20W     | 1450lm | 73lm/W   | 1480lm | 74lm/W   | 1500lm | 75lm/W   |

## **Optional Accessories**



#### **EM Test Button**

SKU:-BU

-Pre installed test button for emergency battery backup



#### JBox Emergency Battery Backup

SKU:-EMJB12W

- External Jbox Emergency battery backup
- Delivery up to 900 lumen for 90 min emergency use

For the accessories detail, please visit www.lironlighting.com/add-on-accessories






## **2DD Series** 2nd Gen Disk Downlight

| Fixture Type: |  |
|---------------|--|
| Project Name: |  |
| Location:     |  |
| Date:         |  |

#### **Wiring Diagram**

CORD/ SUOOLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/products/led2dd for the complete luminaire installation guide.

| Note: |  |  |
|-------|--|--|
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |

