

## **Fixture Type:**

**Project Name:** 

Location:

Date:

#### **Features**

- -CCT adjustable option by dip switch (3000K/3500K/4000K)
- -Wattage selectable option 27W/34W/40W
- -Split design of LED light engine and trim, one engine allows for seamless integration fo multiple trim option
- -Aluminum reflector with white finish ring available in 4",6",8" with round, square and wall wash trim type option.
- -Simple installation with spring action housing clips integrated J-box for direct wire eliminated recessed can










#### **Product Performance Standard**

$3\frac{1}{2}$ " L X $\varnothing 4\frac{1}{8}$ "	Power Factor	90%	
4 lb	LED lifespan	50,000 Hrs	
Recessed	Dimmable	1-10V Dimmable	
ЗССТ	Energy Star	YES	
80	Warranty	5 Years	
120-277V	Ambient Operation Temperature	-20C° (4°F) ~40C °(104°F)	
	4 lb Recessed 3CCT 80	4 lb LED lifespan  Recessed Dimmable  3CCT Energy Star  80 Warranty  Ambient Operation	

## **Dimension**



40W NONIC

**Ordering Guide Example: LED2CD-UW3CCT-40W** 

Wattage Color Temp. Fixture Type Max Wattage 3CCT LED2CD UW = 27W/34W/40W (30K/35K/40K) =Maximum Wattage (Wattage Selectable) (Color Temp. 40 Watts Switchable)

Trim Size

4ST=4" Square Trim

6ST=6" Square Trim

Add-on Accessories

4RT=4' Round Trim Blank = No Accessories 6RT=6' Round Trim EM = Emergency Battery 8RT=8' Round Trim

Backup (A-EMBK8VHV-EXT Field installed only)

4RWT=4" Wall Wash Round Trim CDFRAME-01= Suitable for 6" 6RWT=6"Wall Wash Round round trim only 4SWT=4"Wall Wash Square Trim CDFRAME-02= Suitable for 4" 6SWT=6"Wall Wash Square or 8" round trim only

LED2CD Rev 3-7-2022 PAGE 1 of 4



Fixture Type:
Project Name:
Location:

Date:

#### **Product Information**

3000K 3500K 4000K **WATTAGE LUMEN EFFICACY LUMEN EFFICACY LUMEN EFFICACY** 27W 2160lm 80lm/W 80lm/W 2160lm 2160lm 80lm/W 2550lm 34W 80lm/W 2550lm 80lm/W 2550lm 80lm/W 40W 3000lm 80lm/W 3000lm 80lm/W 3000lm 80lm/W

### **Optional Accessories**



#### **External Emergency Battery Backup**

SKU: EMBK8WH-A-EXT02

- External Emergency battery backup
- Delivery up to 640 lumen for 90 min emergency use
- Field installed only



#### New construction frame

- -SKU: CDFRAME-01
- Suitable for 6" round trim only



#### New construction frame

- -SKU: CDFRAME-02
- Suitable for 4" or 8" round trim only





• .					
ıvt		lacksquare		2	<b>&gt;</b> •
ixt	VI.	C I	y	U	₹•
			//		

**Project Name:** 


Location:

Date:

## **Optional Trim**













8"Round Trim






4"Round Wall Washer






6"Round Wall Washer






4"Square Wall




6"Square Wall








4"Square Wall Washer



6"Square Wall Washer






Fixture Type:	
Project Name:	
Location:	
Date:	

## **Wiring Diagram**

CORD/ SUPPLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/products/led2cd for the complete luminaire installation guide.



Note: