

## CRH Series Dusk to Dawn Road Light

#### **Fixture Type:**

**Project Name:** 

Location:

Date:

#### **Features**

- Heavy-duty cast aluminum housing
- Traditional cobra head appearance
- Removable door 3G vibration rated to ensure strength of construction and longevity in application
- Integral 10kV surge suppression protection standard
- 3 Pin photocell pre-installed
- Available in type III distribution







#### **Product Performance Standard**

Size	24"LX10 1/4"W X 4 1/2"H	Power Factor	≥90%
Weight	10 lb	LED Lifespan	50,000 Hrs
IP Rate	IP66	Dimmable	1-10V Dimmable
Color Temp	4000K-5000K	Light Distribution	11/111
CRI	70	Warranty	5 Years
Input Voltag	• 120-277V/347-480V	Ambient Operation Temperature	-40C° (-40°F) ~45C °(113°F)

#### **Dimension**





Ordering Guide Example: LEDCRH 45W 50K

Fixture Type	Wattage	Color Temp.	Voltage	Finish	Distribution Type
	_			_	
LEDCRH	45W	40K=4000K	Blank = 120-277V	Standard Finish:	3 = Type III
	70W	50K=5000K	HV = 347 -480V	Blank = Silver Grey  1 Premium Finish:	
	100W			DB = Dark Bronze	
	150W			BK =Black	
				WH=White	

Note: 1. Premium finish incur on additional cost, contact factory for MOQ and availability.

Last updated: 6-13-2022

PAGE 1 of 3





Fixture Type:
Project Name:
Location:
Date:

#### **Product Information**

.

4000K		5000K			
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	
45W	6300lm	140lm/W	6350lm	141lm/W	
70W	9300lm	133lm/W	9400lm	134lm/W	
100W	13600lm	136lm/W	13800lm	138lm/W	
150W	19500lm	132lm/W	20000lm	133lm/W	

#### Accessories



#### Twist lock Photocell Included

-SKU: ALPC

-3 PIN twist lock photocell included

For the accessories detail, please visit www.lironlighting.com/add-on-accessories






# CRH Series Dusk to Dawn Road Light

Fixture Type:
Project Name:
Location:
Date:

### **Wiring Diagram**

CORD/ SUPPLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/products/ledcrh for the complete luminaire installation guide.

Note:		

