

LEDCRH Series Cobra Head Road Light

Fixture Type:

Project Name:

Location:

Date:

Features


- Heavy-duty cast aluminum housing
- Traditional cobra head appearance
- Removable door 3G vibration rated to ensure strength of construction and longevity in application
- Integral 10kV surge suppression protection standard
- 3 Pin photocell pre-installed
- Available in type III distribution



Product Performance Standard

Size	20.8in x 8.14in x 4.27in	Power Factor	≥90%
Weight	10 lb	LED Lifespan	50,000 Hrs
IP Rate	IP66	Dimmable	1-10V Dimmable
Color Temp	4000K-5000K	Light Distribution	III
CRI	70	Warranty	5 Years
Input Voltage	120-277V/347-480V	Ambient Operation Temperature	-40C° (-40°F) ~45C °(113°F)

Ordering Guide Example: LEDCRH-70W40K3



Note: 1. Premium finish incur on additional cost, contact factory for MOQ and availability.

Last updated: 8-11-23 PAGE 1 of 3









LEDCRH Series Cobra Head Road Light

Fixture Type:

Project Name:

Location:

Date:

Product Information

	4000K		5000K		
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	
70W	9800lm	140m/W	9900lm	141m/W	
105W	14490lm	138lm/W	14595lm	139lm/W	
150W	19500m	131lm/W	20000m	133lm/W	

Accessories




Twist lock Photocell Included


-SKU: ALPC -3 PIN twist lock photocell included

For the accessories detail, please visit www.lironlighting.com/add-on-accessories


Dimensions

70W/105W





150W







LEDCRH Series Cobra Head Road Light


Fixture Type:

Project Name:

Location:

Date:

Wiring Diagram





Scan the QR code or visit www.lironlighting.com/products/ledcrh for the complete luminaire installation guide.

Note:

