

Fixture Type:

Project Name:

Location:

Date:

Features

- CCT adjustable option by dip switch (3000K, 4000K, 5000K)
- 110-277VAC Input Option
- Split design of led light engine and trim, one engine allows for seamless integration of multiple trim options
- Trim sizes: 4", 6", 8"
- Trim types: round, square and wall wash
- Simple Installation with spring-action housing clips
- Integrated J-Box for direct wire eliminated recessed can, perfect and economic solution for new construction applications.
- 5 years limited warranty













Dimension



Product Performance Standard

Size	$3\frac{1}{2}$ " L X Ø $4\frac{1}{8}$ "	Power Factor	≥90%
Weight	1 lb	LED lifespan	50,000 Hrs
Mounting	Recessed	Dimmable	1-10V Dimmable
Color Temp	3CCT/Single Color Temp.	Energy Star	YES
CRI	80	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~40C°(104°F)

Ordering Guide Example: LED2CD 15W40K



LED2CD Rev 3-7-2022 PAGE 1 of 4



Fixture Type:
Project Name:
Location:
Date:

Product Information

	3000K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
15W	1125lm	75lm/W	1170lm	78lm/W	1200lm	80lm/W
20W	1500lm	75lm/W	1560lm	78lm/W	1600lm	80lm/W

Optional Accessories



Emergency Battery Backup

- -SKU: A-EMBK8WHV-EXT
- -External battery backup is field installed.
- -90min for emergency use.



New construction frame

- -SKU: CDFRAME-3/4/6
- -New construction frame 3"/4"/6"





Fixture Type:

Project Name:

Location:

Date:

Optional Trim




4"Round Trim






6"Round Trim





8"Round Trim






4"Round WallWasher






6"Round Wall Washer






4"Square Wall






6"Square Wall






4"Square Wall Washer





6"Square Wall Washer






Fixture Type:
Project Name:
Location:
Date:

Wiring Diagram

CORD/ SUPPLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/products/led2cd for the complete luminaire installation guide.



Note: