

Fixture Type:

Project Name:

Location:


Date:

Features

- Durable polycarbonate housing
- Polycarbonate latches
- Includes sealed conduit adaptor for 1/2" conduit
- Ribbed frosted polycarbonate lens
- 0-10V dimming driver
- Surface mount
- Compatible with motion sensor



Dimension



Product Performance Standard

Size	2FT	Power Factor	≥90%
Weight	6 lb	LED lifespan	50,000 Hrs
Color Temp	4000K	Dimmable	0-10V Dimming
CRI	80	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~56C° (133°F)

Ordering Guide

Example: LED2VT 4FT 45W 50K

Fixture Type	Size&Wattage	Color Temp.	Voltage	Finish	Optional Accessories
LED2VT	2FT 25 W	40K=4000K	Blank = 120-277V	Blank =White	Blank = No Accessories MS = Motion Sensor (BL-PIR618-EX)

Fixture Type:

Project Name:

Location:

Date:

Product Information

		4000K		5000K	
LENGTH	WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY
2'	25W	3075lm	123lm/W	3125lm	125lm/W

Optional Accessories**PIR - Motion Sensor**

- SKU: BL-PIR618-EX
- Suitable for wet location
- External PIR Motion Sensor is field installed or pre-installed by request.


For the accessories detail, please visit www.lironlighting.com/add-on-accessories

Fixture Type:
Project Name:
Location:
Date:

Wiring Diagram

CORD/ SUPPLY WIRING

LUMINAIRE



Scan the QR code or visit
www.lironlighting.com/product/led2vt
 for the complete luminaire installation guide.

Note:
