



Features

- Large LED flood light with 7Hx6V NEMA distributions
- 1-10V dimming driver
- Rugged die-cast aluminum housing
- Vented housing separated LEDs module from driver, maximizing fixture lifespan and performance
- Door frame seals to housing with a continuous extruded silicone gasket
- Slipfitter or trunnion mount
- Compatible with photocell



Dimension



Product Performance Standard

Size	6 1/8" LX 11" W X 5" H	Power Factor	≥90%
Weight	7 lb	LED Lifespan	50,000 Hrs
IP Rate	IP65	Dimmable	1-10V Dimmable
Color Temp	4000K-5000K	Photometry	7Hx6V
CRI	70	Warranty	5 Years
Input Voltage	120-277V/347-480V	Ambient Operation Temperature	-40C° (-40°F) ~40C° (104°F)

Ordering Guide

Example: LEDLFL 70W 40K

Fixture Type	Wattage	Color Temp.	Voltage	Finish	Mounting	Optional Accessories
LEDLFL	70W 100W	40K=4000K 50K=5000K	Blank = 120-277V HV = 347-480V	Standard finish: Blank = Dark Bronze 1 Premium finish: BK = Black WH = White	TM = Trunnion SP = Slipfitter	Blank = No Accessories 2PC = Photocell (-WPPC)

Note: 1. Premium finish incur on additional cost, contact factory for MOQ and availability.
2. Photocell only suitable for standard voltage 120-277V.

Product Information

4000K			5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY
70W	8900lm	127lm/W	9000lm	127lm/W
100W	13300lm	133lm/W	13400lm	133lm/W

Optional Accessories



Internal Photocell

-SKU: WPPC

-Internal photocell is field installed or pre-installed by request.

For the accessories detail, please visit www.lironlighting.com/add-on-accessories

Mounting Options




Slipfiter Mount -

SKU: SP


- Fit 2-3/8" horizontal

tenon arm




Trunnion Mount

-SKU: TM



Fixture Type:
Project Name:
Location:
Date:

Wiring Diagram



Scan the QR code or visit www.lironlighting.com/product/ledlfl for the complete luminaire installation guide.

Note:
