

## SFL Series Small Flood Light

## **Fixture Type:**

**Project Name:** 

Location:

Date:

#### **Features**

- Small LED flood light with 7H\*6V NEMA distributions
- Rugged die-cast aluminum housing
- Vented housing separated LEDs module from driver, maximizing fixture lifespan and performance
- Door frame seals to housing with a continuous extruded silicone gasket
- Knuckle or trunnion mount option
- Compatible with photocell













#### **Product Performance Standard**

| Size          | 4″L X 6″W X 2 ¹/₄″H | Power Factor                  | 90%                            |
|---------------|---------------------|-------------------------------|--------------------------------|
| Weight        | 2 lb                | LED Lifespan                  | 50,000 Hrs                     |
| IP Rate       | IP65                | Dimmable                      | Non Dimmable                   |
| Color Temp    | 4000K-5000K         | NEMA Type                     | 7H*6V                          |
| CRI           | 70                  | Warranty                      | 5 Years                        |
| Input Voltage | 120-277V            | Ambient Operation Temperature | -40C° (-40°F)<br>~40C °(104°F) |

### **Dimension**



 $2^{1}/_{4}$ inch (65mm)



**Ordering Guide** Example: LEDSFL 15W 40K

| Fixture Type | Wattage | Color Temp. | Voltage                      | Finish              | Mounting      | Optional Accessories   |
|--------------|---------|-------------|------------------------------|---------------------|---------------|------------------------|
|              | -       | <del></del> |                              |                     | _ –           | _                      |
| LEDSFL       | 15W     | 40K=4000K   | Blank = 120-277V             | Standard finish:    | TM = Trunnion | Blank = No Accessories |
|              | 27W     | 50K=5000K   |                              | Blank = Dark Bronze | KN = Knuckle  | PC = Photocell         |
|              |         |             | <sup>1</sup> Premium finish: |                     | (-WPPC)       |                        |
|              |         |             |                              | BK = Black          |               |                        |
|              |         |             |                              | WH = White          |               |                        |

Note: 1. Premium finish incur on additional cost, contact factory for MOQ and availability.

LEDSFL Rev 12-5-2022 PAGE 1 of 3





# SFL Series Small Flood Light

| Fixture Type: |  |
|---------------|--|
| Project Name: |  |
| Location:     |  |

Date:

### **Product Information**

|         | 4000K  |          | 5000K  |          |  |
|---------|--------|----------|--------|----------|--|
| WATTAGE | LUMEN  | EFFICACY | LUMEN  | EFFICACY |  |
| 15W     | 2000lm | 133lm/W  | 2100lm | 134lm/W  |  |
| 27W     | 3600lm | 133lm/W  | 3700lm | 134lm/W  |  |

### **Optional Accessories**



#### **Internal Photocell**

- -SKU: WPPC
- -Internal photocell is field installed or pre-installed by request.


For the accessories detail, please visit www.lironlighting.com/add-on-accessories

## **Mounting Options**



#### **Knuckle Mount**


-SKU: KN





#### **Trunnion Mount**

-SKU: TM



PAGE 2 of 3






| Fixture Type: |
|---------------|
| Project Name: |
| Location:     |
| Date:         |

## **Wiring Diagram**

CORD/ SUPPLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/product/ledsfl for the complete luminaire installation guide.

| Note: |  |  |
|-------|--|--|
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |

