

LEDACUWP Series

LED Adjustable Full Cutoff Wall Pack

Fixture Type:
Project Name:
Location:
Date:

Features

- Die-cast aluminum housing with removeable aluminum back box
- Dark bronze powder coat finish
- Polycarbonate optical lens with UV stabilizer
- 0 to 90 degree tilt adjustable to meet the needs of customers with different light angles
- J box or surface mounting
- Estimated 50,000 hour LED lifespan based on IES LM-80 result and TM-21 calculation
- Optional for internal photocell
- Suitable for wet location



27W & 40W



67W & 80W




Product Performance Standard

Size	7.9in x 8.8in x 7.2in	Power Factor	90%
Weight	Small:4lb Large:7lb	Life Span	50,000 Hrs
IP Rate	IP65	Dimmable	0-10V Dimmable
Color Temp	4000K/5000K	Efficacy	Up to 134 lm/W
CRI	70	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~ 40° (104°F)

Ordering Guide

Example: LEDACUWP-45W50K-PC



LEDACUWP Series

LED Adjustable Full Cutoff Wall Pack

Fixture Type:

Project Name:






Location:

Date:


Product Information

		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	
40W	5200lm	130lm/W	5200lm	130lm/W	
67W	8800lm	131lm/W	8800lm	131lm/W	
80W	10500lm	134lm/W	10500lm	131lm/W	

Dimension



Net Weight:
27W: 3.351lb
40W: 3.968lb



Net Weight:
67W: 7.319lb
80W: 7.804lb

Optional Accessories



Internal Button Photocell

- SKU: WPPC
- Internal Photocell is field installed or pre-installed by request

For the accessories detail, please visit www.lironlighting.com/product_categories/add-on-accessories