

# **PST4 Series** Corolla Post Top

## **Fixture Type:**

Project Name:

Location:

Date:

### **Features**

- Corolla style post top
- Die cast aluminum housing
- Black polyester powder coat finish
- Frosted lens
- Fit to standard 3" diameter pole
- Type V optic distribution
- 0-10V dimming driver
- Compatible with motion sensor















### **Product Performance Standard**

Size	38"LX19"W	Power Factor	≥90%
Weight	20 lb	LED Lifespan	50,000 Hrs
IP Rate	IP65	Dimmable	0-10V Dimming
Color Temp	4000K-5000K	THD	<20%
CRI	70	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~40C°(104°F)

## **Dimension**







**Ordering Guide** Example: LEDPST4 60W 50K

Fixture Type	Wattage	Color Temp.	Voltage	Finish	Optional Accessories
					_
LEDPST4	30 W	30K = 3000K	Blank = 120-277V	Blank = Black	Blank = No Accessories
	60 W	40K = 4000K			MS = Motion Sensor
	120W	50K = 5000K			(-BL-PIR-INT)





Fixture Type:
Project Name:
Location:
Date:

### **Product Information**

\_

3000К		4000K		5000K		
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
30W	3600lm	122lm/W	3750lm	125lm/W	3900lm	130lm/W
60W	7398lm	121lm/W	7483lm	122lm/W	7800lm	130lm/W
120W	14754lm	121lm/W	14937lm	122lm/W	15600lm	130lm/W

### **Optional Accessories**



#### **PIR - Motion Sensor**

- -SKU: BL-PIR-INT
- -Internal PIR Motion Sensor is field installed or pre-installed by request.

For the accessories detail, please visit www.lironlighting.com/product\_categories/add-on-accessories






Fixture Type:
Project Name:
Location:
Date:

### **Wiring Diagram**

CORD/ SUPPLY WIRING LUMINAIRE





Scan the QR code or visit www.lironlighting.com/products/ledpst4 for the complete luminaire installation guide.

Note:		

