

Features



- Heavy duty die-cast aluminum housing with UV stabilized polyester powder paint finish
- Dynamic thermal management design that maximizes heat dissipation
- Built in surge suppression
- NEMA 4HX4V distribution
- 0-10V dimming driver
- Low glare shields provided
- Adjustable trunnion mount
- Optional 2 3/8" Yoke mount adaptor



Product Performance Standard

Size	20" L X 16" W X 15" H	Power Factor	≥90%
Weight	37 lb	LED lifespan	100,000 Hrs
IP RATE	IP65	Dimmable	0-10V Dimmable
Color Temp	4000K-5000K	NEMA	4H*4V
CRI	70	Warranty	10 Years
Input Voltage	120-277V / 277-480V	Ambient Operation Temperature	-40C° (-40°F) ~55C° (131°F)

Dimension



Ordering Guide Example: LED SPL 350W 50K

Fixture Type	Wattage	Color Temp.	Voltage	Finish	Optional Accessories
LED SPL	350W	40K=4000K	Blank = 120-277V	Blank = Black	Blank = No Accessories
	505W	50K=5000K	HV = 277 -480V		YMSPL=Yoke Mount Adapter

Fixture Type:
Project Name:
Location:
Date:

Product Information

4000K				5000K	
Wattage	EPA	LUMEN	EFFICACY	LUMEN	EFFICACY
350W	0.8218	50750lm	145lm/W	51000lm	146lm/W
505W	0.8218	69690lm	138lm/W	70000lm	139lm/W

Optional Accessories



Yoke Adaptor
-SKU: YM-SPL
-Provided to apply the fixture on a 2³/₈" tennon for easy installtion.



Aiming Sight(Included)


For the accessories detail, please visit www.lironlighting.com/product_categories/add-on-accessories

Fixture Type:
Project Name:
Location:
Date:

Wiring Diagram

CORD/ SUPPLY WIRING

LUMINAIRE



Scan the QR code or visit www.lironlighting.com/products/ledspl for the complete luminaire installation guide.

Note:
