

UHB1 Series LED UFO High Bay

Fixture	Type
----------------	------

Project Name

Location:

Date:

Features

- Durable die-cast aluminum housing and heat dissipating fins for excellent thermal control
- Impact resistant tempered glass
- Black powder coat finish
- Wattage selectable 200W/150W/100W
- Color temperature of 5000K
- Efficacy up to 170 LPW
- 5 years warranty









Hook













Product Performance Standard

Size	13.2 X 7.5inch	Power Factor	90%
Weight	6 lb	Life Span	50,000 Hrs
IP Rate	IP65	Dimmable	1-10V Dimmable
Color Temp	5000K	Efficacy	Up to 170 lm/W
CRI	70	Warranty	5 Years
Input Voltage	100-277V	Ambient Operation Temperature	-40C° (-40°F) ~ 50C° (122°F)

Dimensions





Ordering Guide Example: UHB1 UW 50K

Fixture Type	Wattage	Color Temp.	Voltage	¹Finish	Optional Accessories
			_		_
UHB1	UW	50K = 5000K	Blank = 100-277V	Blank = Black	Blank = No accessories
	200/150/100W				MS = Motion Sensor
	Wattage Selectable				EM = Emergency
					Battery Backup





UHB1 SeriesLED UFO High Bay

Fixture Type:		
Project Name		
Location:		
Date:		

Product Information

	5000K		
WATTAGE	LUMEN	EFFICACY	
100W	1 <i>7</i> ,000lm	170lm/W	
150W	25,500lm	170lm/W	
200W	34,000lm	170lm/W	

Optional Accessories



Internal Motion Sensor

- Internal motion sensor is field installed or pre-installed by request



External Emergency Battery Backup

- External battery backup is field installed or pre-installed by request
- Delivery 900 lumen for 90 minutes emergency operation



Aluminum Reflector

For the accessories detail, please visit www. lironlighting.com/product_categories/add-on-accessories





UHB1 SeriesLED UFO High Bay

Fixture Type:	
Project Name	
Location:	

Wiring Diagram

Black Line

White Neutral

Green/Yellow Green Ground

Purple DIM+

Gray

DIM-



Date:

Scan the QR code or visit www.lironlighting.com/product/uhb1 for the complete luminare installation guide.

NOTE:	
NOIL.	

