

SP2 Series

LED Strips Light

Fixture Type:	
Project Name:	
Location:	
Date:	

Features

- LED 2' and 4' strip light
- Durable cold rolled steel housing whit white coat finish
- Frosted white diffuser lens
- Wattage selectable
- 3CCT color temperature adjustable 3000K/4000K/5000K
- 130 lumens per watt
- Universal 120-277V input voltage
- Surface mount or suspension mount(1FT chain hanger included)
- 4ft to 8ft row connector available
- Optional motion sensor and emergency battery backup available












Product Performance Standard

Size	2FT /4FT	Dimming	0-10V Dimming	
Weight	4 lb/6 lb	Life Span	50,000 Hrs	
Color Temp	3CCT 30/40/50K Efficacy		130 lm/W	
CRI	RI 80 W		5 Years	
Input Voltage	120-277V	Ambient Operation Temperature	-13C° (-4°F) ~ 40° (104°F)	

Dimensions

24"(600mm)

47" (1200mm)



Ordering Guide Example: SP2-4FTUW3CCT

Fixture Type	Length	Wattage	/attage CCT Voltage		Optional Accessories
_	-	_	_	_	
SP2	2FT	UW	3CCT =	Blank = 100-277V	Blank = No accessories
	4FT	2′ 15/20/25W	Color temperature		EXMS =External Motion Sensor
		4′ 27/36/45W	adjustable		(BL-PIR819-EX)
			30/40/50K		INMS=Internal Motion Sensor
					(BL-810MW-IN)
					EM = Emergency Battery Backup
					RC-SP2 = Row Connector
					6FT Aircraft Cable
					WG-SP2=Wire Guard



SP2 Series

LED Strip Light

Fixture Type:
Project Name:
Location:
Date:

Product Information

		3000K		4000K		5000K	
LENGTH	WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
2′	15W	1905lm	127lm/W	1920lm	128lm/W	1950lm	130lm/W
	20W	2540lm	127lm/W	2560lm	128lm/W	2600lm	130lm/W
	25W	31 <i>75</i> lm	127lm/W	3200lm	128lm/W	3250lm	130lm/W

		30	00К	40	4000K 5000K		00K
LENGTH	WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
4′	27W	3429	127lm/W	3456	128lm/W	4550lm	130lm/W
	36W	4572	127lm/W	4608	128lm/W	5200lm	130lm/W
	45W	5715	127lm/W	5760	128lm/W	5850lm	130lm/W

Optional Accessories



Internal Motion Sensor

- SKU: BL-810MW-IN
- Internal motion sensor is pre-installed by request



External Motion Sensor

- SKU: BL-PIR819-EX
- External motion sensor is pre-installed by request



Internal Emergency Battery Backup

- SKU: EMBK8WL-A-INT01
- Internal battery backup is pre-installed by request
- -Delivery 1000 lumen for 90 minutes emergency operation



Row Connector 4ft to 8ft

- SKU: RC-SP2-4FTUW3CCT
- To convert a 4ft fixture to 8ft fixture





SP2 Series

LED Strip light

Fixture Type:

Project Name:

Location:

Date:



Wire Guard

-SKU: WG-SP2



1FT Chain Hanger


- Included



6FT aircraft cable

- SKU: AircraftCable-VT4/SP2-6FT

Wiring Diagram





Scan the QR code or visit www.lironlighting.com/product/SP2 for the complete installation guide.

