

UHB3 SeriesLED UFO HIGH BAY

Fixture	Type:

Project Name

Location:

Date:

Features

- UHB3 is a compact and streamlined designed, which allows for efficient heat dissipation and better airflow.
- Durable die-cast aluminum housing with corrosion-resistant black powder coating which prolong the lifespan of the LEDs and ensure reliable performance over an extend period.
- Anti-UV prismatic translucent lens is specially designed to shape light uniformly and control glare
- Wattage selectable provide flexibility in lighting design, allowing you to customize the illumination levels for different areas and tasks.
- 2CCT color temperature adjustable 4000K/5000K.
- Available for hook mount (Default)/pendant mount (3/4" conduit size)(optional

)/surface mount(Optional)

- IP65 rating suitable for wet location.













Product Performance Standard

Size	14.1 in x 7.5 in	Power Cord length	2 FT	
Weight	12 lb	Conduit Size	3/4 inch	
IP Rate	IP65	Dimmable	1-10V Dimmable	
Color Temp	3CCT or 2CCT	Efficacy	Up to 140 lm/W	
CRI	80	Warranty	5 Years	
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~ 45C° (113°F)	

Easy to access the lumen output and color temperature switch on-site.

Ordering Guide Example: UHB3-UW3CCT-210W

Fixture Type	Wattage	Color Temp.	Color Temp. Maximum Wattage		Accessories	
		-	_	_		
UHB3	UW	2CCT	150W	Blank = No MS or EM	Blank = No Acces-	
	= Wattage Selectable	= 4000/5000K	= Maximum wattage 150 Watt	MS = Motion Sensor	sories	
		Color Temp. Adjustable	210W	(BL-ANT5-4T-PIR)	UHB3-ALREFELECTOR	
		¹ 3CCT	= Maximum wattage 210 Watt	EM = Emergency	=Aluminum Reflector	
		=3000K/4000K/5000K		Battery Backup	² U-BRACKET-UHB3	
		Color Temp. Adjustable		(EMBK-UHB3-15W for 150W)	=U Bracket for Surface	
				(EMBK-UHB3-25W for 210W)	mount	

1.3CCT only available in 210W.

2.U-BRACKET is not supported when EM installed.

Last updated:9-12-2023





UHB3 SeriesLED UFO High Bay


Fixture Type:			
Project Name			
Location:			
Date:			


Product Information

	30	3000K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY	
210W	30000lm	143lm/W	30500lm	145lm/W	32000lm	152lm/W	
168W	24500lm	146lm/W	25000lm	149lm/W	26500lm	158lm/W	
126W	19000lm	151lm/W	20000lm	159 lm/W	21000lm	167lm/W	
84W	13500lm	161lm/W	14000lm	167lm/W	14500lm	173lm/W	

	30	3000K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY	
150W	22000lm	147lm/W	24000lm	160lm/W	22500lm	150lm/W	
120W	18000lm	150lm/W	20000lm	167lm/W	19000lm	158lm/W	
90W	14000lm	156lm/W	15500lm	172lm/W	14600lm	162lm/W	
60W	9800lm	163lm/W	10800lm	180lm/W	10000lm	167lm/W	

Dimensions







UHB3 SeriesLED UFO High Bay

Fixture	Type:
----------------	-------

Project Name

Location:

Date:

Optional Accessories





Plug and play PIR Motion Sensor

- SKU: BL-ANT5-4T-PIR
- Motion sensor is pre-installed by request



External Emergency Battery Backup

- SKU:EMBK-UHB3-15W(For 150W)
- SKU:EMBK-UHB3-25W(For 210W)
- External battery backup is field installed only
- 90 minutes emergency operation



Aluminum Reflector

-SKU: UHB3-ALREFLECTOR



U-Bracket

-SKU:U-BRACKET-UHB3

For the accessories detail, please visit www. lironlighting.com/product_categories/add-on-accessories

