

VT4 Series

LED Vapor Tight Wattage Selectable & 3CCT

Fixture Type:

Project Name

Location:


Date:

Features

- 2FT wattage selectable and 3CCT vapor tight.
- High impact resistant acrylic prismatic lenses attached with stainless steel clips, enhancing the airtight seal.
- Wattage selectable 15W/20W/25W
- Color temperature adjustable 3000K/4000K/5000K
- 0-10V dimmable
- 3/4" knockouts hole for easier installation
- Weather proof fixture - IP65 Rated suitable for wet location
- Optional accessories internal motion sensor and internal emergency battery backup




Dimensions



Product Performance Standard

Size	23.6" x 5" x 3.54"	Power Factor	90%
Weight	4 lb	Life Span	50,000 Hrs
IP Rate	IP65	Dimmable	0-10V Dimmable
Color Temp	3CCT	Efficacy	Up to 130 lm/W
CRI	70	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-20C° (-4°F) ~ 40C° (104°F)



Ordering Guide

Example: VT4-2FTUW3CCT-25W

Fixture Type	Length	Wattage	3CCT	Voltage	Wattage Options	Optional Accessories
VT4	2FT = 2 ft	UW = Wattage Selectable	3CCT = Color Temperature Selectable	Blank = 120-277V	25W = Maximum Wattage	Blank = No accessories MS = Motion Sensor (BL-810MW-IN) EM = Emergency Battery Backup (EMBK8WL-S-INT01)

VT4 Series

LED Vapor Tight Wattage Selectable & 3CCT

Fixture Type:

Project Name

Location:

Date:

Product Information

2'		3000K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY	EFFICACY
25W	3175lm	127lm/W	3225lm	129lm/W	3250lm	130lm/W	130lm/W
20W	2540lm	127lm/W	2580lm	129lm/W	2600lm	130lm/W	130lm/W
15W	1905lm	127lm/W	1935lm	129lm/W	1950lm	130lm/W	130lm/W

Optional Accessories



Internal Motion Sensor

SKU:BL-810MW-IN

- Internal motion sensor is field installed or pre-installed by request



Internal Emergency Battery Backup

SKU:EMBK8WL-S-INT01

- External battery backup is pre-installed by request
- Delivery 1040 lumen for 90 minutes emergency operation


For the accessories detail, please visit www.lironlighting.com/product_categories/add-on-accessories

VT4 Series

LED Vapor Tight Wattage Selectable & 3CCT

Fixture Type:
Project Name
Location:
Date:

Wiring Diagram



Installation Instructions

<p>1. Drill four holes into the screw locations on the ceiling.</p>	<p>2. Fix the plastic anchor into the ceiling, insert the screws into the metal clamp, then fix the screws into the anchor</p>
<p>3. Fix the fixture into the clamps shown as above</p>	<p>4. Complete the installation as the above picture shown</p>
<h3>Wiring</h3> <p>L (Live Line) GND (Ground) N (Null Line)</p>	

Warning: Turn off the power before installation