


UHB3 Series

LED UFO HIGH BAY

Fixture Type:
Project Name
Location:
Date:

Features

- UHB3 is a compact and streamlined designed, which allows for efficient heat dissipation and better airflow.
- Durable die-cast aluminum housing with corrosion-resistant black powder coating which prolong the lifespan of the LEDs and ensure reliable performance over an extend period.
- Anti-UV prismatic translucent lens is specially designed to shape light uniformly and control glare
- Wattage selectable provide flexibility in lighting design, allowing you to customize the illumination levels for different areas and tasks.
- 2CCT color temperature adjustable 4000K/5000K.
- Available for hook mount(Default)/pendant mount(3/4" conduit size)(optional)/surface mount(Optional).
- Standard 120-277V, optional step down transformer convert to high voltage mode.
- IP65 rating suitable for wet location.



Easy to access the lumen output and color temperature switch on-site.



Product Performance Standard

Size	14.1 in x 7.5 in	Power Cord length	6 FT
Weight	12 lb	Conduit Size	3/4 inch
IP Rate	IP65	Dimmable	1-10V Dimmable
Color Temp	2CCT	Efficacy	Up to 140 lm/W
CRI	80	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~ 45C° (113°F)

Ordering Guide

Example: UHB3-UW3CCT-210W

Fixture Type	Wattage	Color Temp.	Maximum Wattage	Voltage	Motion & EM	Accessories
UHB3	UW = Wattage Selectable	2CCT = 4000K/5000K Color temp. adjustable	150W = Max Watt 150W 210W =Max Watt 210W 230W =Max Watt 230W	Blank = 120-277V HV =347-480V	Blank = No accessories MS = Motion Sensor (BL-ANT5-4T-PIR) ¹ EM = Emergency Battery Backup (EMBK-UHB3-15W) (EMBK-UHB3-25W)	Blank = No accessories ALRFELECTOR = Aluminum Reflector ² Bracket-UHB3 =U bracket for surface mount

1. EM is not support when fixture in high voltage.
2. EM is not support when the U bracket installed.



UHB3 Series

LED UFO High Bay

Fixture Type:

Project Name

Location:

Date:

Product Information

UHB3-150W

WATTAGE	4000K		5000K	
	LUMEN	EFFICACY	LUMEN	EFFICACY
150W	24000lm	160lm/W	22500lm	150lm/W
120W	20000lm	167lm/W	19000lm	158lm/W
90W	15500lm	172lm/W	14600lm	162lm/W
60W	10800lm	180lm/W	10000lm	167lm/W


UHB3-210W

WATTAGE	4000K		5000K	
	LUMEN	EFFICACY	LUMEN	EFFICACY
210W	32000lm	152lm/W	30500lm	145lm/W
168W	26500lm	158lm/W	25000lm	149lm/W
126W	21000lm	167lm/W	20000lm	159lm/W
84W	14500lm	173lm/W	14000lm	167lm/W


UHB3-230W

WATTAGE	4000K		5000K	
	LUMEN	EFFICACY	LUMEN	EFFICACY
230W	36000lm	157lm/W	36000lm	157lm/W
184W	30000lm	163lm/W	29000lm	158lm/W
138W	24000lm	174lm/W	23000lm	167lm/W
92W	16500lm	179lm/W	16000lm	174lm/W

Dimensions



150W



210W/230W

UHB3 Series

LED UFO High Bay

Fixture Type:

Project Name

Location:

Date:

Optional Accessories



Plug and play PIR Motion Sensor

- SKU: BL-ANT5-4T-PIR

- Motion sensor is pre-installed by request



External Emergency Battery Backup

- SKU:EMBK-UHB3-15W(For 150W)

- SKU:EMBK-UHB3-25W(For 210W/230W)

- External battery backup is field installed only

- 90 minutes emergency operation



U-Bracket

-SKU:U-BRACKET-UHB3



Aluminum Reflector

-SKU: UHB3-ALREFLECTOR

For the accessories detail, please visit www.lironlighting.com/product_categories/add-on-accessories


Mounting



Hook Mount (Default Mounting)



Conduit Mount (Optional)



Surface Mount (Optional)

Fixture Type:

Project Name:


Location:

Date:



Plug-and-Play Sensor (optional)
Sensor allows for security and energy saving.

Emergency Battery
25W 3500lm 90min



Installation accessory

Available for both hook mount, conduit mount and surface mounting with U-bracket(optional). U-bracket allows to adjust the direction to illuminate any area you need.

Transformer BOX

Transformer can be easily added into the Junction-box and convert to HV models, reducing SKUs and inventory pressure.

Housing

Rugged die-cast housing with corrosion-resistant powder coating for effective protection.