

VT5 Series

LED 8FT Vapor Tight Wattage Selectable & 3CCT

Fixture Type: Project Name Location: Date:

Features

- High impact resistant acrylic prismatic lenses attached with stainless steel clips, enhancing the airtight seal
- Wattage selectable 40/60/80W
- Color temperature adjustable 3000K/4000K/5000K
- 0-10V dimmable
- 3/4" knockouts hole for easier installation
- Weather proof fixture IP65 Rated suitable for wet location
- Optional accessories internal motion sensor and emergency battery backup
- 5 Year warranty














Product Performance Standard

_			4 •		
Size	47.2" × 5" × 3.54"	Power Factor	90%		
Weight	8 lb	Life Span	50,000 Hrs		
IP Rate	IP65	Dimmable	0-10V Dimmable		
Color Temp	3CCT	Efficacy	Up to 130 lm/W		
CRI	70	Warranty	5 Years		
Input Voltage	120-277V	Ambient Operation Temperature	-20C° (-4°F) ~ 40C° (104°F)		

Dimensions



ued

Ordering Guide Example: VT5-8FTUW3CCT-80W

Fixture Type	Length	Wattage	3CCT	Voltage	Wattage Options	Optional Accessories
	_	_		_		_
VT5	8FT = 8 FT	UW	3CCT	Blank	80W	Blank = No accessories
		= Wattage	= Color	= 120-277V	= 8FT Maximum	MS = Motion Sensor
		Selectable	Temperature	HV	Wattage 80W	(ANT-3A)
			Selectable	=480V		EM = Emergency Battery
						Backup
						(EMBK-TF-AC8W)

Last updated: 1-4-2023





VT5 Series

LED 8FT Vapor Tight Wattage Selectable & 3CCT

Fixture Type:	
Project Name	
Location:	
Date:	

Product Information

	300	3000K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY	
40W	5040lm	126lm/W	5120lm	128lm/W	5200lm	130lm/W	
60W	7560lm	126lm/W	<i>7</i> 680lm	128lm/W	7800lm	130lm/W	
80W	10080lm	126lm/W	10240lm	128lm/W	10400lm	130lm/W	

Optional Accessories



- Internal motion sensor is field installed or pre-installed by request

- Internal battery backup is pre-installed by request

- Delivery 1,040 lumen for 90 minutes emergency operation

For the accessories detail, please visit www. lironlighting.com/product_categories/add-on-accessories

