

LED Linear High Bay

Fixture Type:				
Project Name				
Location:				

Date:

Features

- Enhance durability and thermal control through full-body construction with a centralized driver housing.
- Standard white polyester powder coat finish post-fabrication to enhance durability and inhibit rust.
- A presimatic lens offers additional protection and controls glare.
- 3 different size with wattage selectable function.
- Plug and play motion sensor and internal emergency battery backup available.
- Suitable for damp location.

















Dimensions





WATTAGE	Α	В	С	D
400W	12.8"	45.67"	0.91"	2.08"
300W	12.8"	35.34"	0.91"	2.08"
220W	12.8"	23.76"	0.91"	2.08"

Specification

Material	Sheet metal housing	Efficacy	Up to 140 lm/W	
Lens	Presimatic Lens	LED Life Span	88.73% lumen maintenance @ 50,000 hrs	
Beam angle	100 degree	Dimmable	0-10V Dimming	
IColor Temp	3CCT 3500K/4000K/5000K	Lumen Package	18,200 lm to 56,000 lm	
CRI	70	Warranty	5 Years	
Input Voltage	120-277V or 277-480V	Ambient Operation Temperature	-40C° (-40°F) ~45° (113°F)	
Installation	Chain mount 3FT length & 2 V-hanger brackets included. Optional surface mount and extension chain is available.	Listing	DLC Premium UL Listed Damp location listed	






LED Linear High Bay

Fixture Type:	Fixture Type:				
Project Name					
Location:					
Date:					

Ordering Guide

Example: LHB5-UW3CCT-300W-EM25W-MS01-WG300W-SFM



Note: 1. EM25 is not available for 220W LHB5 fixtures.

2. HVEM30 is only suitable for 347-480V LHB5 fixtures.





LED Linear High Bay

	Fixture Type:			
	Project Name			
	Location:			
-	Date:			

Product Information

LHB5-UW3CCT-220W 3500K		00K	4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
220W	30360lm	138lm/W	30360lm	138lm/W	30800lm	140lm/W
175W	24150lm	138lm/W	24150lm	138lm/W	24500lm	140lm/W
130W	17940lm	138lm/W	17940lm	138lm/W	18200lm	140lm/W

LHB5-UW3CCT-300W 3500K		00К	40	00K	5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
300W	41400lm	138lm/W	41400lm	138lm/W	42000lm	140lm/W
275W	37950lm	138lm/W	37950lm	138lm/W	38500lm	140lm/W
255W	35190lm	138lm/W	35190lm	138lm/W	35700lm	140lm/W

LHB5-UW3CCT	LHB5-UW3CCT-400W 3500K		4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
400W	55200lm	138lm/W	55200lm	138lm/W	56000lm	140lm/W
300W	41400lm	138lm/W	41400lm	138lm/W	42000lm	140lm/W
220W	30360lm	138lm/W	30360lm	138lm/W	30800lm	140lm/W





LED Linear High Bay

Project Name

Location:

Date:

Optional Accessories

Emergency Battery Backup:

Internal 8W Emergency Battery Backup SKU: EMBK8W-CNP02

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 1100 lumen during emergency mode



Internal 15W Emergency Battery Backup SKU: EMBK-LHB5-15W

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 2100 lumen during emergency mode



Internal 25W Emergency Battery Backup SKU: EMBK-LHB5-25W

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 3500 lumen during emergency mode



Internal 40W Emergency Battery Backup SKU:EMBK-LHB-40W

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 5,600 lumen during emergency mode



External 30W Emergency Battery Backup for High Voltage Fixture

- External battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 4,200 lumen during emergency mode
- Only suitable for high voltage fixture





LED Linear High Bay

Fixture	Type:

Project Name

Location:

Date:

Motion Sensor:



3 PIN PIR Plug and Play Motion Sensor 12/24V SKU: ANT3IN-PIR

- 3PIN infrared motion sensor 12-24V DC
- Factory default setting: 100% sensitivity, Hold time 5min, Dimming level: 30%, Dimming time: 60mins.



3 PIN Microwave Plug and Play Motion Sensor 12/24V SKU: ANT3IN-MIC

- -3PIN microwave motion sensor12-24V DC
- -Factory default setting: 100% sensitivity, Hold time 5min, Dimming level: 30%, Dimming time: 60mins.


Wire Guard:



Wire Guard

SKU: WG-LHB5-220W - Wire guard for 220W LHB5 WG-LHB5-300W - Wire guard for 300W LHB5 WG-LHB5-400W - Wire guard for 400W LHB5

Mounting Option:



Surface Mount Kit

SKU: LHB5-SFM

-Surface mount kit for use LHB5 fixture



Extension Chain

SKU: EXCHAIN-LHB5

-3ft chain extension with connection link lock

