# LiRON LiGHTING

## WKL5 Series
LED 4″ Temporary Disk Light

## Features

-4″ LED temporary disk light.
-Two screws and quick connects make installtion easy.
-Steel housing with diffusion lens for optimal visual confort.
-Equipped standard with 120V on-board module.
-4″ models are designed for mounting on standard junction box.
-Suitable for damp location



## Product Performance Standard

| Size | 4.13″x0.024″x0.59″ | Power Factor | 90% |
|---|---|---|---|
| **Weight** | 1 lb | **Lift Span** | 27,000 Hrs |
| **Wattage** | 10 Watts | **Dimmable** | 0-10V Dimmable |
| **Color Temp** | 4000K | **Efficacy** | Up to 70 lm/W |
| **CRI** | 80 | **Warranty** | 3 Years |
| **Input Voltage** | 120V | **Ambient Operation Temperature** | -20C° (-4°F) ~ 40C° (104°F) |

## Ordering Guide    Example: WKL5-4IN10W40K

| Fixture Type | | Size & Wattage | | Color Temp. | | Voltage |
|---|---|---|---|---|---|---|
| | — | | — | | — | |
| WKL5 | | 4IN10W = 4INCH 10Watts | | 40K =4000K | | Blank =120V |

# LiRON LiGHTING

## WKL5 Series
LED 4" Temporary Disk Light

**Fixture Type:**

**Project Name**

**Location:**

**Date:**

## Product Information

| 4000K | | |
|---|---|---|
| **WATTAGE** | **LUMEN** | **EFFICACY** |
| 10W | 700lm | 70lm/W |

## Dimensions

**10835 S Wilcrest Dr, Ste C Houston TX 77099** | Customer Service : 833-875-4766 | Email : Sales@lironlighting.com

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.lironlighting.com for most current technical information.