

FCWP5L Series

LED WATTAGE & 3CCT SELECTABLE FULL CUT OFF WALL PACK

Fixture Type:

Project name:

Location:




Date:

Features

- Full cutoff design ensures that all emitted light is directed downward, reducing light pollution and preventing light trespass.
- Rugged cast-aluminum housing provides durability and longevity, making it resistant to corrosion, rust, and other environmental factors .
- Field wattage selectable (Maximum wattage: 125W) allow for adjustable power consumption based on specific lighting needs, providing flexibility and energy saving.
- 3CCT color temperature adjustable 3000/4000/5000K
- Operated on standard voltages of 120-277V AC, optionally compatible with high voltages through the use of a step down transformer, allowing flexibility for installation in various settings.
- Optional emergency battery, photocell and motion sensor available.
- Built to withstand harsh weather conditions, ensuring reliable performance in various outdoor environment.



Dimensions



Net Weight
70W: 7.21lb
125W: 7.68lb

Specification

Material	Rugged cast aluminum housing	Efficacy	Up to 168 lm/W
Lens	Tempered UV coated flat lens	LED Life Span	50,000 hrs based on TM-21 calculation
Beam angle	90 degree	Dimmable	0-10V Dimming
Color Temp	3CCT 3000K/4000K/5000K	Lumen Package	4,700 lm to 10,200 lm(70W) 8,100 lm to 18,000lm(125W)
CRI	70	Warranty	5 Years
Input Voltage	120-277V Optional 347-480V by used the step down transformer	Ambient Operation Temperature	-40°C (-40°F) ~45° C(113°F)
Installation	Wall mount	Listing	UL Listed IP65



FCWP5L Series

LED WATTAGE & 3CCT SELECTABLE FULL CUT OFF WALL PACK

Fixture Type:


Project name:

Location:

Date:


Ordering Guide

Example: FCWP5L-UW3CCT-125W-EM8-MS01-PC



Note: 1. Premium finish incur on additional cost, contact factory for MOQ and availability.

Optional Accessories





FCWP5L Series

LED WATTAGE & 3CCT SELECTABLE FULL CUT OFF WALL PACK

Fixture Type:

Project name:

Location:

Date:

Product Information

FCWP5-UW3CCT-125W 3000K			4000K		5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY	LUMEN	EFFICACY
125W	17,100lm	137lm/W	19,000lm	152lm/W	18,000lm	144lm/W
100W	14,200lm	142lm/W	15,700lm	157lm/W	15,000lm	150lm/W
75W	11,000lm	147lm/W	12,100lm	161lm/W	11,700lm	156lm/W
50W	7,600lm	152lm/W	8,200lm	164lm/W	8,100lm	162lm/W

Fixture Type:

Project name:

Location:

Date:

Optional Accessories

Emergency Battery Backup:



Internal 8W Emergency Battery Backup

SKU: EMBK8WH-A-INT01

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 1100 lumen during emergency mode
- Suitable 70W



Internal 8W Emergency Battery Backup

SKU: EMBK8W-CNP02

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 1100 lumen during emergency mode
- Suitable for 125W

Motion Sensor:



Internal PIR Motion Sensor

SKU: BL-PIR823-IN

- Passive infrared motion sensor pre-install by request
- Factory default setting: 100% sensitivity, Hold time 10 sec ,daylight sensor is 30 lux, Dimming level: 30%, Dimming time: 60mins.

Photocell:



Button Photocell

SKU: WPPC

- Photocell enables the fixtures to turn on at dusk and off at dawn.
- Reduce energy consumption and extends fixture life span.
- Factory internal pre-install by request.



FCWP5L Series

LED WATTAGE & 3CCT SELECTABLE FULL CUT OFF WALL PACK

Fixture Type:

Project name:

Location:

Date:

High Voltage Step Down Transformer:



High Voltage Step Down Transformer

SKU: TRANS-480V

- Step down transformers
- Used when needing to take a higher 347-480V AC voltage down to lower 240V ac voltage.