

LED Wall Cylinder Downlight only Wattage selectable and 5CCT

Features

- A perfect blend of elegance and efficiency LED wall cylinder, offers superior brightness and energy efficiency compared to traditional lighting solution.

- 4" round head sizes with down light options, catering to various aesthetic preferences and spatial requirements.

- Wattage selectable and 5CCT adjustable that suits your lighting needs, ensuring optimal brightness and energy efficiency.


- 60 degree beam angle provides a wide and even light distribution, minimizing shadows and dark spots for a well -lit environment.


- Optional emergency battery backup , providing additional safety.

- Suitable for wet location.



Dimensions





	Α	В	С
WCS41	4"	7.4"	4.72″

Specification

Material	Rugged cast aluminum housing	Efficacy	Up to 100 lm/W
Lens	Polycarbonate Lens	LED Life Span	50,000 hrs
Beam angle	60 degree	Dimmable	0-10V Dimming
IColor Temp	5CCT 2700K/3000K/3500K/4000K/5000K	Lumen Package	600 lm to 1,800 lm
CRI	70	Warranty	5 Years
Input Voltage	110-277V	Ambient Operation Temperature	-20°C (-4°F) ~45° C(113°F)
Installation	Wall mount	Listing	ETL IP6 <i>5</i>

Fixture Type:

Project Name

Location:

Date:



WCS41- Rev 06-18-2024



LED Wall Cylinder Downlight only Wattage selectable and 5CCT


Fixture Type:

Project Name

Location:

Date:

Ordering Guide Example: WCS41-5CCT-EM8



Optional Accessories

internal pre-install.

Photocell Emergency Battery Backup PC EM8 (SKU:WCS-EMBK-8W) = 8W Emergency battery backup,

=Internal Photocell pre-install

WCS41- Rev 06-18-2024



LED Wall Cylinder Downlight only Wattage selectable and 5CCT

Product Information

Fixture Type:

Project Name

Location:

Date:

WCS41-4"Downlight		5000K	
WATTAGE	LUMEN	EFFICACY	
13W	1300lm	100lm/W	
10W	1000lm	100lm/W	
7W	700lm	100lm/W	



LED Wall Cylinder Downlight only Wattage selectable and 5CCT

Optional Accessories

Emergency Battery Backup:



Internal 4W Emergency Battery Backup SKU: WCS-EMBK-4W

- Internal battery backup is pre-install by request
- 90 minutes emergency operation
- Provide up to 400 lumen during emergency mode

Photocell:



Internal Photocell

- Internal photocell is pre-install by request
- Dusk to dawn photocell control.

Fixture Type:

Project Name

Location:

Date: