

LED Round Cylinder Light - Surface Mount

Fixture Type:

**Project Name** 

Location:

Date:

### Features

- Modular design
- Aluminum housing acting as the heat sink to maximize life
- Constructed of rigid die-cast aluminum. Powder coated polyester that comes standard in white and black finish
- Cylinder beam-spreads are interchangeable which can be easily swapped out in the field without tools
- Wattage selectable (maximum wattage: 4" 25W, 6" 40W and 8" 58W) allows for adjustable power consumption based on specific lighting needs, providing flexibility and energy saving
- 2700K, 3000K, 3500K, 4000K with a great color consistency
- Power factor >0.9
- For interior use only



5 YEAR		White	Copper	Chrome	Black	
Specification		White	Copper	Chrome	Black	
Housing	Rigid die-cast aluminum housing	Efficacy	Efficacy Up to 105 lm/W			
Lens	COB LED	LED Life Span	LED Life Span		50,000 Hrs	
Beam angle:	15°, 24°, 36°, 60° options	Dimmable	Dimmable		0-10V Dimmable	
Color Temp	2700K/3000K/3500K/4000K	Lumen Package	Lumen Package		1,140lm to 5,220lm	
CRI	80+	Warranty	Warranty		5 Years	
Input Voltage	120-277V	Ambient Opera Temperature	Ambient Operation Temperature			
Installation	Surface Mount	Listing		Damp Location		



LED Round Cylinder Light - Surface Mount

## Fixture Type:

**Project Name** 

Location:


Date:

Ciuc	ring Guide Examp	le: <b>CYL1-440K-15D-V</b>			
SKU	Size	Color Temperature	Beam Angle	Trims	Finish
CYL1	4= 4" wattage	27K= 2700K	15D= 15°	WB	WH
	selectable	30K= 3000K		= White Baffle	= White
	12/18/25W	35K= 3500K	24D= 24° 36D= 36°	BB = Black Baffle	ВК
	/ / -/	40K= 4000K	36D= 36°	СВ	= Black
	6= 6" wattage	401-40001	00D= 00°	= Copper Baffle CHB	
	selectable			= Chrome Baffle	
	20/30/40W				
	8= 8" wattage				
	selectable				
	29/44/58W				
Mou	inting Option:	Optional Acc	essories:		
	Mounting	EM			
	DIOL				
	RJSM = Surface mount	EM			
	= Surface mount = 8W Emerge with recessed Driver operating				
	J-box	120 minu			
		(EMBK8WH-A	-EXTO2)		
	Mars				
	= Surface with surface				
	mount 4"				
	octagonal				
	junction box				



LED Round Cylinder Light - Surface Mount

### Dimensions











5%10



71/10

## Mounting Option

#### Surface Mounted To Recessed J-Box



4"/6"/8"

#### Surface Mounted Conduit Cutout To Surface J-Box



## Fixture Type:

**Project Name** 

Location:

Date:



LED Round Cylinder Light - Surface Mount

### Trim Option



### Performance Data

Dimension	Wattage Selectable	Efficacy	Lumens
4"	25w/18w/12w	95lm/w	1140~2350lm
6"	40w/30w/20w	105lm/w	2100~4200lm
8"	58w/45w/30w	90lm/w	2610~5220lm

### **Optional Accessories**



#### 8W Emergency Driver

- SKU: EMBK8WH-A-EXTO2
- Operating for lighting up to 120 minutes

## Fixture Type:

Project Name

Location:

Date: