

ALR-Recessed Slim Linear







FIXTURE TYPE:
 PROJECT NAME:
 LOCATION:
 DATE:

SLIM LINEAR RECESSED MOUNT LINEAR LUMINAIRE



Dimensions



Specification

Material	Extruded aluminum housing
Lens	PC
Beam angle	110 degree
Color Temp	3CCT 3000K/3500K/4000K
CRI	80
Input Voltage	110-277V
Installation	Recessed mount
Efficacy	Up to 100lm/W
LED Life Span	50,000 hours
Dimmable	0-10V Dimming
Lumen Package	1,700lm to 8,000lm
Warranty	5 Years
Ambient Operation Temperature	-20°C(-4°F) to 40°C (104°F)
Listing	UL Listed, Damp Location

ALR-Recessed Slim Linear

FIXTURE TYPE:	
PROJECT NAME:	
LOCATION:	
DATE:	

SLIM LINEAR RECESSED MOUNT LINEAR LUMINAIRE

Features

- Slim and linear design delivers a clean, modern aesthetic that seamlessly integrates into any space.
- Offered in 2ft, 4ft, and 8ft lengths with up to 1000 lm/ft, providing powerful and flexible linear lighting solutions.
- Available in popular 4" and 6" widths to fit a variety of ceiling designs and applications.
- Wattage selectable (50% / 75% / 100%) for optimized energy management.
- Adjustable CCT (3000K, 3500K, 4000K) allows for versatile use across different environments and preferences.

Ordering Guide Sample: ALR-4FT4IN3CCT-EM

Fixture Type	Length	Width	CCT	Finish
ALR	2FT = 2FT (20W/15W/10W Selectable) 4FT = 4FT (40W/30W/20W Selectable) 8FT = 8FT (80W/60W/40W Selectable)	4IN = 4inch 6IN = 6inch	3CCT =3000/3500/4000K	Blank = White

Optional Accessories

Emergency Battery Backup

EM
 (SKU: EMBK15WH-A-EXT02) =
 15W Emergency battery backup

Flange Mount Kit

ALR-4FT4IN-FM
 =4ft 4inch flange mount kit
 ALR-4FT6IN-FM
 =4ft 6inch flange mount kit
 ALR-8FT4IN-FM
 =8ft 4inch flange mount kit
 ALR-8FT6IN-FM
 = 8ft 6inch flange mount kit

FIXTURE TYPE:
 PROJECT NAME:
 LOCATION:
 DATE:

SLIM LINEAR RECESSED MOUNT LINEAR LUMINAIRE

Performance Data

Width	Length	Wattage Selectable	Efficacy@4000K	Lumen@4000K
4inch	2ft	20W/15W/10W	85lm/w, 850lm/ft	Up to 1700lm
	4ft	40W/30W/20W	90lm/w, 900lm/ft	Up to 3600lm
	8ft	80W/60W/40W	90lm/w, 900lm/ft	Up to 7200lm

Width	Length	Wattage Selectable	Efficacy@4000K	Lumen@4000K
6inch	2ft	20W/15W/10W	100lm/w, 1000lm/ft	Up to 2000lm
	4ft	40W/30W/20W	100lm/w, 1000lm/ft	Up to 4000lm
	8ft	80W/60W/40W	100lm/w, 1000lm/ft	Up to 8000lm

Optional Accessories

Emergency Battery Backup:



Emergency Battery Backup

SKU: EMBK15WH-A-EXT02

- 15W external emergency battery backup require field install.



Flange Mount Kit

SKU: ALR-4FT6IN-FM/ALR-4FT4IN-FM/ALR-8FT6IN-FM/ALR-8FT4IN-FM

- Flange mount kit 4ft and 8ft only.